Eaton 170M2090



Catalog Number: 170M2090

Fuse-link, high speed, 100 A, DC 2400 V, size 3, 83 x 93 x 268 mm, aR, IEC, single indicator

00 00

EAN

145 mm

383.8 g

Product Weight

Product Name Catalog Number Eaton Bussmann series high speed 170M2090 traction fuse UPC 051712533959 Product Length/Depth 5027590303989 268 mm **Product Height Product Width** 83 mm

Certifications IEC 60269-4



00 00

Fuse indicator

Other

Rated voltage DC

2400 V

Interrupt rating

100 kAIC

Construction size

1

Center-to-center distance of connections

246 mm

Color

None

Current type

DC

Material

Ceramic

Release characteristic

Other

Amperage Rating

100 A

Mounting dimension

M8

Utilization category

aR (accompanied semiconductor protection)

Frequency rating - max

62 Hz

Туре

Fuse

Fuse system (according to IEC 60269) Other

Fuse shape

Square body, offset bolted tags

Breaking capacity

0 kA

Frequency rating - min

00

45 Hz

Class

Class aR

Voltage rating

2400 V

Application

traction

third rail

Voltage type

DC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights property of their respective Reserved.

Eaton is a registered trademark.

All other trademarks are

owners.



Eaton.com/socialmedia