Eaton 170M3388

Catalog Number: 170M3388

Fuse-link, high speed, 50 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, single indicator





Eaton Bussmann series high speed

square body fuse

UPC

051712255851

Product Length/Depth

75 mm

Product Width

45 mm

Warranty

Not Applicable

Certifications

IEC Rated

UL Recognized

Catalog Number

170M3388

Model Code

FUSE 50A 1250V 1*BKN/75 AR CU

EAN

5027590447386

Product Height

59 mm

Product Weight

352.25 g

Compliances

CE Marked

RoHS Compliant



Interrupt rating

100 kAIC

Center-to-center distance of connections

74 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

Flush

Amperage Rating

50 A

Fuse type

Flush end

BKN/75 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A

Fitted with:

Type K Indicator for micro

Fuse size

1*

Voltage rating

1250 V (IEC), 1300 V (UL)

Fuse indicator

Centre fuse status indicator

Construction size

Other

Clearing (I2T)

815 at 1000 V, 1100 at 1250 V

Rated voltage AC

1250 V

Color

None

Mounting dimension

M8

Utilization category

aR (accompanied semiconductor protection)

Watt losses

15 W

Type

Fuse

Fuse shape

Square body, flush end contacts

Breaking capacity

100 kA

Class

Class aR

Pre arc (I2T)

135

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia