

Eaton 170M7636

Catalog Number: 170M7636

Fuse-link, high speed, 1500 A, AC 1000 V, 200 kA, size 4, 105 x 120 x 95 mm, aR, IEC, type K indicator

□ □



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M7636
	UPC
	051712683562
EAN	Product Length/Depth
5996516021736	95 mm
Product Height	Product Width
105 mm	120 mm
Product Weight	Compliances
2729 g	CE
	RoHS Compliant
	EAC
Certifications	
IEC 60269-4	

Fuse indicator

Centre fuse status indicator

Interrupt rating

200 kAIC

Construction size

4

Clearing (I²T)

3600000 at 1000 V

Rated voltage AC

1000 V

Center-to-center distance of connections

87.6 mm

Color

None

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

Flush

Amperage Rating

1500 A

Mounting dimension

M10

Utilization category

aR (accompanied semiconductor protection)

Watt losses

250 W

Fuse type

Flush end

BKN/95 Type K Indicator

Type

Fuse

Fuse system (according to IEC 60269)

Other

Breaking capacity

200 kA

Fuse size

4

Class

Class aR

Pre arc (I2T)

600000

Voltage rating

1000 V (IEC)

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)