



### 3AG Normal-Blo Fuse

3AG (311) series Normal-Blo fuses are for use in radios, amplifiers, etc. Features straight type fuse element positioned to center of fuse for easy identification of blown fuse.

**Voltage Rating:** 32V.

| US & Canadian Boxed No. | US Carded No. | Voltage Rating | Description        |
|-------------------------|---------------|----------------|--------------------|
| V 311005                | 311005 BP     | 32V            | 5A 3AG Normal-Blo  |
| V 311010                | 311010 BP     | 32V            | 10A 3AG Normal-Blo |
| V 311015                | 311015 BP     | 32V            | 15A 3AG Normal-Blo |
| V 311025                | 311025 BP     | 32V            | 20A 3AG Normal-Blo |

### 8AG Normal-Blo Fuse

8AG (362) series Normal-Blo fuses are smaller in size ( $\frac{1}{4}$ " x 1") and are designed to be used where space limitations prevent the use of 3AG fuses.

**Voltage Rating:** 32V.

**Approvals:** UL listed:  $\frac{1}{8}$  – 5A, CSA Certified:  $\frac{1}{4}$  – 5A.

| US & Canadian Boxed No. | US Carded No. | Voltage Rating | Description       |
|-------------------------|---------------|----------------|-------------------|
| V 362002                | 362002 BP     | 32V            | 2A 8AG Normal-Blo |
| V 362005                | 362005 BP     | 32V            | 5A 8AG Normal-Blo |

### 3AB Fast-Acting & Slo-Blo® Ceramic Fuse

Ceramic body construction permits higher interrupting and voltage ratings. Ideal for applications where high current loads are expected.

**Voltage Rating:** 250V ( $\frac{1}{8}$  – 20A), 125V (25 – 30A).

**Approvals:** UL listed and CSA Certified:  $\frac{1}{8}$  – 15A, Recognized under the Components Program of UL: 20 – 30A.

| US & Canadian Boxed No. | US Carded No. | Voltage Rating | Description         |
|-------------------------|---------------|----------------|---------------------|
| V 314010                | 314010 BP     | 250V           | 10A 3AB Fast-Acting |
| V 314015                | 314015 BP     | 250V           | 15A 3AB Fast-Acting |
| V 314020                | 314020 BP     | 250V           | 20A 3AB Fast-Acting |
| V 326015                | 326015 BP     | 250V           | 15A 3AB Slo-Blo     |

### 3AG Shock-Safe Panel Fuseholders

Designed to eliminate the possibility of electrical shock, as defined in IEC standards 65 and 257. Shock-Safe fuseholders feature a low profile body, finger-grip knob and anti-tease feature that eliminates circuit interruption when knob is accidentally depressed.

**Voltage Rating:** 250V.

**Approvals:** UL listed and CSA Certified. Recognized under the Components Program of UL.

| US & Canadian Boxed No. | US Carded No. | Canadian Carded No. | Amp Rating (Max) | Description   |
|-------------------------|---------------|---------------------|------------------|---|
| 3453LF8A                | 3453LF8C      | 3453LF8CA           | 20A              | with $\frac{1}{4}$ " straight NEMA/DIN Quick Connect Terminal |
| 3453LF2A                | 3453LF2C      | 3453LF2CA           | 20A              | with $\frac{3}{16}$ " straight dual purpose solder terminal   |
| 346877                  | 346877C       | 346877CA            | 15A              | Flip top 3AG Fuseholder                                       |
| 348877                  | 348877C       | 348877CA            | 15A              | Low profile Snap Mount 3AG Fuseholder                         |