


5KP-HR Series

Axial Leaded – 5 kW



Agency Approvals

| Agency | Agency File Number |
|--------|--------------------|
| | E230531 |

Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|--|-----------------|------------|--------------------|
| Peak Pulse Power Dissipation by 10/1000 μs Test Waveform (Fig.2)(Note 1) | P_{PPM} | 5 | kW |
| Steady State Power Dissipation on Infinite Heat Sink at $T_A=75^\circ\text{C}$ | P_D | 8.0 | W |
| Peak Forward Surge Current, 8.3ms Single Half Sine Wave Unidirectional Only (Note 2) | I_{FSM} | 400 | A |
| Maximum Instantaneous Forward Voltage at 100A for Unidirectional Only (Note 3) | V_F | 3.5/5.0 | V |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 175 | $^\circ\text{C}$ |
| Typical Thermal Resistance Junction to Lead | $R_{\theta JL}$ | 8.0 | $^\circ\text{C/W}$ |
| Typical Thermal Resistance Junction to Ambient | $R_{\theta JA}$ | 40 | $^\circ\text{C/W}$ |

Notes:

- Non-repetitive current pulse per Fig. 4 and derated above T_J (initial) = 25°C per Fig. 3.
- Measured on 8.3ms single half sine wave or equivalent square wave, duty cycle=4 per minute maximum.
- $V_F < 3.5\text{V}$ for single die parts and $V_F < 5.0\text{V}$ for stacked-die parts.

Description

The 5KP-HR High Reliability Series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

Features & Benefits

- 5 kW peak pulse capability at 10/1000 μs waveform, repetition rate (duty cycles):0.01%
- Glass passivated chip junction in P600 package
- Fast response time: typically less than 1.0ps from 0 Volts to $V_{BR\ min}$
- Excellent clamping capability
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC-61000-4-2 ESD 30kV(Air), 30kV (Contact)
- EFT protection of data lines in accordance with IEC 61000-4-4
- Low incremental surge resistance
- Typical I_R less than $2\mu\text{A}$ when $V_{BR\ min} > 12\text{V}$
- High temperature soldering guaranteed: 260C/10 seconds / 0.375" (9.5mm) lead length, 5 lbs., (2.3kg) tension
- $V_{BR} @ T_J = V_{BR} @ 25^\circ\text{C} \times (1 + \alpha T \times (T_J - 25))$ (αT : Temperature Coefficient, typical value is 0.1%)
- UL Recognized compound meeting flammability rating V-0
- Lead-free matte tin plated package
- Halogen free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/JEDEC J-STD-609A.01)

Applications

TVS Components are ideal for the protection of I/O interfaces, V_{CC} bus and other vulnerable circuits used in telecom, computer, industrial and consumer electronic applications.

Functional Diagram



Bi-directional




Uni-directional

5KP-HR Series

Axial Leaded – 5 kW

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

| Part Number (Uni) | Part Number (Bi) | Reverse Stand off Voltage V_R (Volts) | Breakdown Voltage V_{BR} (Volts) @ I_T | | Test Current I_T (mA) | Maximum Clamping Voltage V_C @ I_{PP} (V) | Maximum Peak Pulse Current I_{PP} (A) | Maximum Reverse Leakage I_R @ V_R (μA) | Agency Recognition  |
|-------------------|------------------|---|--|--------|-------------------------|---|---|---|--|
| | | | MIN | MAX | | | | | |
| 5KP5.0A-HR | 5KP5.0CA-HR | 5.0 | 6.40 | 7.00 | 50 | 9.2 | 554.3 | 5000 | X |
| 5KP6.0A-HR | 5KP6.0CA-HR | 6.0 | 6.67 | 7.37 | 50 | 10.3 | 495.1 | 5000 | X |
| 5KP6.5A-HR | 5KP6.5CA-HR | 6.5 | 7.22 | 7.98 | 50 | 11.2 | 455.4 | 2000 | X |
| 5KP7.0A-HR | 5KP7.0CA-HR | 7.0 | 7.78 | 8.60 | 50 | 12.0 | 425.0 | 1000 | X |
| 5KP7.5A-HR | 5KP7.5CA-HR | 7.5 | 8.33 | 9.21 | 5 | 12.9 | 395.3 | 250 | X |
| 5KP8.0A-HR | 5KP8.0CA-HR | 8.0 | 8.89 | 9.83 | 5 | 13.6 | 375.0 | 150 | X |
| 5KP8.5A-HR | 5KP8.5CA-HR | 8.5 | 9.44 | 10.40 | 5 | 14.4 | 354.2 | 50 | X |
| 5KP9.0A-HR | 5KP9.0CA-HR | 9.0 | 10.00 | 11.10 | 5 | 15.4 | 331.2 | 20 | X |
| 5KP10A-HR | 5KP10CA-HR | 10.0 | 11.10 | 12.30 | 5 | 17.0 | 300.0 | 15 | X |
| 5KP11A-HR | 5KP11CA-HR | 11.0 | 12.20 | 13.50 | 5 | 18.2 | 280.2 | 2 | X |
| 5KP12A-HR | 5KP12CA-HR | 12.0 | 13.30 | 14.70 | 5 | 19.9 | 256.3 | 2 | X |
| 5KP13A-HR | 5KP13CA-HR | 13.0 | 14.40 | 15.90 | 5 | 21.5 | 237.2 | 2 | X |
| 5KP14A-HR | 5KP14CA-HR | 14.0 | 15.60 | 17.20 | 5 | 23.2 | 219.8 | 2 | X |
| 5KP15A-HR | 5KP15CA-HR | 15.0 | 16.70 | 18.50 | 5 | 24.4 | 209.0 | 2 | X |
| 5KP16A-HR | 5KP16CA-HR | 16.0 | 17.80 | 19.70 | 5 | 26.0 | 196.2 | 2 | X |
| 5KP17A-HR | 5KP17CA-HR | 17.0 | 18.90 | 20.90 | 5 | 27.6 | 184.8 | 2 | X |
| 5KP18A-HR | 5KP18CA-HR | 18.0 | 20.00 | 22.10 | 5 | 29.2 | 174.7 | 2 | X |
| 5KP20A-HR | 5KP20CA-HR | 20.0 | 22.20 | 24.50 | 5 | 32.4 | 157.4 | 2 | X |
| 5KP22A-HR | 5KP22CA-HR | 22.0 | 24.00 | 26.90 | 5 | 35.5 | 143.7 | 2 | X |
| 5KP24A-HR | 5KP24CA-HR | 24.0 | 26.70 | 29.50 | 5 | 38.9 | 131.1 | 2 | X |
| 5KP26A-HR | 5KP26CA-HR | 26.0 | 28.90 | 31.90 | 5 | 42.1 | 121.1 | 2 | X |
| 5KP28A-HR | 5KP28CA-HR | 28.0 | 31.10 | 34.40 | 5 | 45.4 | 112.3 | 2 | X |
| 5KP30A-HR | 5KP30CA-HR | 30.0 | 33.30 | 36.80 | 5 | 48.4 | 105.4 | 2 | X |
| 5KP33A-HR | 5KP33CA-HR | 33.0 | 36.70 | 40.60 | 5 | 53.3 | 95.7 | 2 | X |
| 5KP36A-HR | 5KP36CA-HR | 36.0 | 40.00 | 44.20 | 5 | 58.1 | 87.8 | 2 | X |
| 5KP40A-HR | 5KP40CA-HR | 40.0 | 44.40 | 49.10 | 5 | 64.5 | 79.1 | 2 | X |
| 5KP43A-HR | 5KP43CA-HR | 43.0 | 47.80 | 52.80 | 5 | 69.4 | 73.5 | 2 | X |
| 5KP45A-HR | 5KP45CA-HR | 45.0 | 50.00 | 55.30 | 5 | 72.7 | 70.2 | 2 | X |
| 5KP48A-HR | 5KP48CA-HR | 48.0 | 53.30 | 58.90 | 5 | 77.4 | 65.9 | 2 | X |
| 5KP51A-HR | 5KP51CA-HR | 51.0 | 56.70 | 62.70 | 5 | 82.4 | 61.9 | 2 | X |
| 5KP54A-HR | 5KP54CA-HR | 54.0 | 60.00 | 66.30 | 5 | 87.1 | 58.6 | 2 | X |
| 5KP58A-HR | 5KP58CA-HR | 58.0 | 64.40 | 71.20 | 5 | 93.6 | 54.5 | 2 | X |
| 5KP60A-HR | 5KP60CA-HR | 60.0 | 66.70 | 73.70 | 5 | 96.8 | 52.7 | 2 | X |
| 5KP64A-HR | 5KP64CA-HR | 64.0 | 71.10 | 78.60 | 5 | 103.0 | 49.5 | 2 | X |
| 5KP70A-HR | 5KP70CA-HR | 70.0 | 77.80 | 86.00 | 5 | 113.0 | 45.1 | 2 | X |
| 5KP75A-HR | 5KP75CA-HR | 75.0 | 83.30 | 92.10 | 5 | 121.0 | 42.1 | 2 | X |
| 5KP78A-HR | 5KP78CA-HR | 78.0 | 86.70 | 95.80 | 5 | 126.0 | 40.5 | 2 | X |
| 5KP85A-HR | 5KP85CA-HR | 85.0 | 94.40 | 104.00 | 5 | 137.0 | 37.2 | 2 | X |
| 5KP90A-HR | 5KP90CA-HR | 90.0 | 100.00 | 111.00 | 5 | 146.0 | 34.9 | 2 | X |
| 5KP100A-HR | 5KP100CA-HR | 100.0 | 110.00 | 123.00 | 5 | 162.0 | 31.5 | 2 | X |
| 5KP110A-HR | 5KP110CA-HR | 110.0 | 122.00 | 135.00 | 5 | 177.0 | 28.8 | 2 | X |
| 5KP120A-HR | 5KP120CA-HR | 120.0 | 133.00 | 147.00 | 5 | 193.0 | 26.4 | 2 | X |
| 5KP130A-HR | 5KP130CA-HR | 130.0 | 144.00 | 159.00 | 5 | 209.0 | 24.4 | 2 | X |
| 5KP150A-HR | 5KP150CA-HR | 150.0 | 167.00 | 185.00 | 5 | 243.0 | 21.0 | 2 | X |
| 5KP160A-HR | 5KP160CA-HR | 160.0 | 178.00 | 197.00 | 5 | 259.0 | 19.7 | 2 | X |
| 5KP170A-HR | 5KP170CA-HR | 170.0 | 189.00 | 209.00 | 5 | 275.0 | 18.5 | 2 | X |
| 5KP180A-HR | 5KP180CA-HR | 180.0 | 200.00 | 221.00 | 5 | 292.0 | 17.5 | 2 | X |
| 5KP190A-HR | 5KP190CA-HR | 190.0 | 211.00 | 233.00 | 5 | 310.0 | 16.5 | 2 | - |
| 5KP200A-HR | 5KP200CA-HR | 200.0 | 222.00 | 246.00 | 5 | 329.2 | 15.5 | 2 | X |
| 5KP210A-HR | 5KP210CA-HR | 210.0 | 233.00 | 258.00 | 5 | 349.5 | 14.6 | 2 | - |
| 5KP220A-HR | 5KP220CA-HR | 220.0 | 244.00 | 270.00 | 5 | 371.1 | 13.7 | 2 | X |

Note:

2. Each lot of parts will pass group B test requirement.

5KP-HR Series

Axial Leaded – 5 kW

Screen Process



| | |
|---|-----------------------------------|
| 100% Vision Inspection | MIL-STD-750 method 2074 |
| 100% High Temperature Storage Life (168hrs,175°C) | MIL-STD-750 method 1031 |
| 100% Temperature Cycle Test (-55 to 150°C, 20 cycles, dwell time 15 min) | MIL-STD-750 method 1051 |
| 100% Surge Test (2x) | MIL-STD-750 method 4066 |
| 100% HTRB 150°C Bias=VR(80% breakdown voltage, 96hrs, and each direction 96hrs for Bi-directional products) | MIL-STD-750 method 1038 |
| Final Electrical Test(100% 3 sigma limit, 100% dynamic test and PAT limit) | MIL-STD-750 method 4016.4021.4011 |

Note: Up-screen program can be specified by customer's request via contacting Littelfuse service

Group B Test Requirement

| Screen | Method | Condition | Requirement |
|------------------|-------------------------------------|---|--|
| Surge test | 10/1000 μ s Peak Pulse Waveform | Maximum clamping Voltage (V_C) @ Peak Pulse Current (I_{PP}) | Sample Size 45 perform 10x Accept 0 failures Sample size 45 |
| Burn - In (HTRB) | MIL -STD-750, Method 1038.5 | Applied voltage 100% V_R @150°C | 340 hours (680 hours for bi-direction products, each direction 340 hours) Accept 0 failures Sample size 45 |
| Electrical test | -- | I_R @ V_R , $V_{(BR)}$ @ I_T | Accept 0 failures |

I-V Curve Characteristics



- P_{PPM} **Peak Pulse Power Dissipation** – Max power dissipation
 V_R **Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
 V_{BR} **Breakdown Voltage** – Maximum voltage that flows through the TVS at a specified test current (I_T)
 V_C **Clamping Voltage** – Peak voltage measured across the TVS at a specified I_{PPM} (peak impulse current)
 I_R **Reverse Leakage Current** – Current measured at V_R
 V_F **Forward Voltage Drop for Uni-directional**

5KP-HR Series

Axial Leaded – 5 kW

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Figure 1 - TVS Transients Clamping Waveform




Figure 2 - Peak Pulse Power Rating Curve




Figure 3 - Peak Pulse Power Derating Curve




Figure 4 - Pulse Waveform




Figure 5 - Typical Junction Capacitance





Figure 6 - Typical Transient Thermal Impedance



5KP-HR Series

Axial Leaded – 5 kW

Figure 7 - Maximum Non-Repetitive Peak Forward Surge Current Uni-Directional Only





Figure 8 - Peak Forward Voltage Drop vs Peak Forward Current (Typical Values)




Physical Specifications

| | |
|-----------------|--|
| Weight | 0.07oz., 2.1g |
| Case | P600 molded plastic body over passivated junction. |
| Polarity | Color band denotes the cathode except Bipolar. |
| Terminal | Matte Tin axial leads, solderable per JESD22-B102. |


Environmental Specifications

| | |
|----------------------------|-------------|
| High Temp. Storage | JESD22-A103 |
| HTRB | JESD22-A108 |
| Temperature Cycling | JESD22-A104 |
| H3TRB | JESD22-A101 |
| RSH | JESD22-B106 |

Part Numbering System



Part Marking System




Packing Options

| Part Number | Component Package | Quantity | Packaging Option | Packaging Specification |
|-------------|-------------------|----------|------------------|-------------------------|
| 5KPxxxXX-HR | P600 | 800 | Tape & Reel | EIA STD RS-296 |

5KP-HR Series

Axial Leaded – 5 kW




P600


Dimensions

| Dimensions | Inches | | Millimeters | |
|------------|--------|-------|-------------|------|
| | Min | Max | Min | Max |
| A | 1.000 | - | 25.40 | - |
| B | 0.340 | 0.360 | 8.60 | 9.10 |
| C | 0.048 | 0.054 | 1.22 | 1.36 |
| D | 0.340 | 0.360 | 8.60 | 9.10 |



Tape and Reel Specification



RTCA/DO-160G Wave 3



RTCA/DO-160G Wave 4 and Wave 5



5KP-HR Series

Axial Leaded – 5 kW

Pin Injection Protection Per RTCA/DO-160G

| Part Number (Uni) | Part Number (Bi) | 25C | | | | | | | 70C | | | | | | | 120C | | | | | | | |
|-------------------|------------------|--------|-------------------|------|------|--------------------|------|-------|--------|-------------------|------|------|--------------------|------|------|--------|-------------------|------|------|--------------------|------|------|------|
| | | Wave 3 | Wave 4 (6.4/69us) | | | Wave 5a (40/120us) | | | Wave 3 | Wave 4 (6.4/69us) | | | Wave 5a (40/120us) | | | Wave 3 | Wave 4 (6.4/69us) | | | Wave 5a (40/120us) | | | |
| | | L5 | L3 | L4 | L5 | L3 | L4 | L5 | L5 | L3 | L4 | L5 | L3 | L4 | L5 | L5 | L3 | L4 | L5 | L3 | L4 | L5 | |
| | | 128A | 60A | 150A | 320A | 300A | 750A | 1600A | 128A | 60A | 150A | 320A | 300A | 750A | 128A | 60A | 150A | 320A | 300A | 750A | 128A | 60A | 150A |
| 5KP5.0A-HR | 5KP5.0CA-HR | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP6.0A-HR | 5KP6.0CA-HR | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP6.5A-HR | 5KP6.5CA-HR | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP7.0A-HR | 5KP7.0CA-HR | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP7.5A-HR | 5KP7.5CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP8.0A-HR | 5KP8.0CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP8.5A-HR | 5KP8.5CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP9.0A-HR | 5KP9.0CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP10A-HR | 5KP10CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP11A-HR | 5KP11CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass |
| 5KP12A-HR | 5KP12CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP13A-HR | 5KP13CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP14A-HR | 5KP14CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP15A-HR | 5KP15CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP16A-HR | 5KP16CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP17A-HR | 5KP17CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP18A-HR | 5KP18CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | pass | - |
| 5KP20A-HR | 5KP20CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP22A-HR | 5KP22CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP24A-HR | 5KP24CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP26A-HR | 5KP26CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP28A-HR | 5KP28CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP30A-HR | 5KP30CA-HR | pass | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP33A-HR | 5KP33CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP36A-HR | 5KP36CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP40A-HR | 5KP40CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP43A-HR | 5KP43CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP45A-HR | 5KP45CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP48A-HR | 5KP48CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP51A-HR | 5KP51CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP54A-HR | 5KP54CA-HR | pass | pass | pass | pass | pass | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP58A-HR | 5KP58CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP60A-HR | 5KP60CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP64A-HR | 5KP64CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP70A-HR | 5KP70CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP75A-HR | 5KP75CA-HR | pass | pass | pass | pass | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP78A-HR | 5KP78CA-HR | pass | pass | pass | - | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP85A-HR | 5KP85CA-HR | pass | pass | pass | - | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP90A-HR | 5KP90CA-HR | pass | pass | pass | - | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP100A-HR | 5KP100CA-HR | pass | pass | pass | - | - | - | - | pass | pass | pass | pass | pass | - | pass | pass | pass | pass | pass | pass | pass | - | - |
| 5KP110A-HR | 5KP110CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP120A-HR | 5KP120CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP130A-HR | 5KP130CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP150A-HR | 5KP150CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP160A-HR | 5KP160CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP170A-HR | 5KP170CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP180A-HR | 5KP180CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP190A-HR | 5KP190CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP200A-HR | 5KP200CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP210A-HR | 5KP210CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |
| 5KP220A-HR | 5KP220CA-HR | pass | pass | - | - | - | - | - | pass | - | - | - | - | - | pass | - | - | - | - | - | - | - | - |

Note:

1. L1 = Level 1, L2 = Level 2, L3 = Level 3, L4 = Level 4, L5 = Level 5

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics.