

# BFMN-D


BFMN is a lower-cost and more compact BFAT



### General Specification

Rated Voltage	DC32V
Breaking Capacity	1000A
Operation Temperature	-40°C~80°C
Standard	ISO8820-3
Country of Origin	Japan
Plating	Ag Plating
Standard Packaging	10,000
Insertion Force	—
Extraction Force	—
Recommended Torque	—

### Dimensions



### Product Lineup

Ampere Rating(A)	Part Number	Housing Colors	Resistance Value	Voltage Drop
1	1281	Black	121 mΩ	175 mV
2	1282	Gray	49.7 mΩ	140 mV
3	1283	Violet	29.6 mΩ	140 mV
4	1284	Pink	23.8 mΩ	136 mV
5	1285	Tan	16.7 mΩ	112 mV
7.5	1286	Brown	11.1 mΩ	112 mV
10	1287	Red	7.82 mΩ	106 mV
15	1288	Blue	4.93 mΩ	99 mV
20	1289	Yellow	3.48 mΩ	95 mV
25	1278	Natural	2.58 mΩ	92 mV
30	1279	Green	2.12 mΩ	86 mV

\*In case a product other than the ones published in this document is desired, please contact us for details.

### Time-Current Characteristic

% of Ampere Rating(A)	Operating Time	
	Min	Max
110%	100hrs.	—
135%	0.75sec.	600sec.
160%	0.25sec.	50sec.
200%	0.15sec.	5sec.
350%	0.04sec.	0.5sec.
600%	0.02sec.	0.1sec.

\*The fuse characteristic may change depending on the conditions of use.

### Time-Current Characteristic Chart

